



WP160B - WP315B



Featuring

- Suitable for PE, PP, PVDF pipes butt welding
- Integrated die casting aluminum clamps, steel base with cylinder, provides stable performance.
- Planing tool with separate switch prevents unintentional operation. Durable and long life HSS blade.
- Heating plate with high quality PTFE coating, enables swift temperature control.

Model	WP160B	WP200B	WP250B	WP315B
Welding range (mm)	63-160	63-200	90-250	110-315
Standard reducers (mm)	63-75-90-110-125-140-160	63-75-90-110-125-140-160-180-200	90-110-125-140-160-180-200-225-250	110-125-140-160-180-200-225-250-280-315
Power supply	220V/50Hz, 1PH	220V/50Hz, 1PH	220V/50Hz, 1PH	220V/50Hz, 1PH
Total power	3.25 KW	3.55 KW	4.15 KW	4.85 KW
Heating plate	1.5 KW	1.8 KW	2.3 KW	3.1 KW
Planing tool	1.0 KW	1.0 KW	1.1KW	1.0KW
Hydraulic station	0.75 KW	0.75 KW	0.75KW	0.75KW
Pressure adjusting range	0-6.3MPa	0-6.3MPa	0-6.3 MPa	0-6.3MPa
MaxTemperature of heating plate	270°C	270°C	270°C	270°C
Temperature Deviation	±5°C	±5°C	±5°C	±5°C