



WP355B - WP500B



Featuring

- Suitable for PE, PP, PVDF pipes butt welding
- Integrated die casting aluminum clamps, steel base with cylinder, provides stable performance.
- Planing tool with separate switch prevents unintentional operation. Durable and long life HSS blade.
- Heating plate with high quality PTFE coating, enables swift temperature control.

Model	WP355B	WP400B	WP450B	WP500B
Welding range (mm)	160-355	160-400	200-450	250-500
Standard reducers (mm)	160-180-200-225-250-280-315-355	160-180-200-225-250-280-315-355-400	200-225-250-280-315-355-400-450	250-280-315-355-400-450-500
Power supply	220V/50Hz, 1PH	380V/50Hz, 3PH	380V/50Hz, 3PH	380V/50Hz, 3PH
Total power	5.3 KW	8.35 KW	9.1 KW	9.1 KW
Heating plate	3.55 KW	6.5 KW	6.5 KW	6.5 KW
Planing tool	1.0KW	1.1KW	1.1KW	1.1KW
Hydraulic station	0.75KW	0.75KW	1.5KW	1.5KW
Pressure adjusting range	0-6.MPa	0-8MPa	0-8MPa	0-8MPa
MaxTemperature of heating plate	270°C	270°C	270°C	270°C
Temperature Deviation	±5°C	±7°C	±7°C	±7°C